

SICO Tri-Height Stage

Three Height adjustments for more flexibility. Set-up at single level for meeting room stages, fashion runways, or head table settings. Set-up tiered configurations for seating or choral risers.

Easy to set-up and take-down:

- Each section rolls in on its own casters and is quickly and easily set into place. The wheels lower automatically and engage to the floor as the unit is folded for storage.

Easy to put together:

- The stage sections lock positively together with unit-to-unit connectors when units are at the same or varying heights. No cords, velcro, or tape are necessary to hold stages in place.

Easy to operate:

- Requires minimal effort to set-up, keeping staffing requirements and labor costs to a minimum.

Easy to Adjust:

- Changing heights is simple with the SICO lock and pin mechanism. Just rotate the yellow handle and adjust to the desired height. Adjusts in 6" (15 cm) increments, adhering to ADA (Americans with Disabilities Act) requirements.

Easy to Change:

- Reversible decks offer a long wearing carpet surface or a scratch resistant Tuff-Deck smooth surface.

Accessories:

- Adjustable step units, ADA ramps, guard rail covers, backdrops and drapes (see pages 10 & 11).

Guard Rails

- This added safety feature must be used with all SICO stages and risers.



All units are fully mobile, with each riding on 5" (13 cm) rubber casters. Four swivel casters allow for easier handling in and out of storage.



Decks nest firmly within the frames, spreading out the load rather than concentrating it in small areas.

SICO Tri-Height Stage Specifications:

S3H316C??41B: 6'x8'-12"/18" (305/457 mm)

S3H316E??41B: 6'x8'-18"/24"/30" (457/610/762 mm)

S3H316F??41B: 6'x8'- 24"/30"/36" (610/762/914 mm)

S3H316G??41B: 6'x8'-30"/36"/42" (762/914/1067 mm)

S3H314C??41B: 4'x8'-12"/18" (305/457 mm)

S3H314E??41B: 4'x8'-18"/24"/30" (457/610/762 mm)

S3H314F??41B: 4'x8'- 24"/30"/36" (610/762/914 mm)

S3H314G??41B: 4'x8'-30"/36"/42" (762/914/1067 mm)